

# MultiLine

## GreenLube Grease

**Use GreenLube Grease for a smooth operation!** This market leader ensures excellent performance and protection of on and off road equipment. GreenLube is designed for use in all automatic greasing systems, no matter what the climate or environment. When used with our MultiLine system, the EP-0 Grease can be used in temperatures of -13F (-25C) and EP-1 Grease can be used in temperatures of -4F (-20C).



### PROTECTS EQUIPMENT FROM:

- ✱ Corrosion
- ✱ Moisture
- ✱ Clogging
- ✱ Heat & Friction
- ✱ Pollutants & Contaminants
- ✱ Severe Environments & Temperatures

**Ask about  
our MultiLine  
GreenLube  
Warranty  
extension  
program!**

### GreenLube Product Listing

#### GreenLube EP-0 Pail

Weight: 35lbs/15.9 KG  
Part #: F122976

#### GreenLube EP-0 Keg

Weight: KG 120 lbs./54  
KG Part#: 08202

#### GreenLube EP-0 Drum

Weight: 386 lbs./175 KG  
Part#: 08402

#### GreenLube EP-1 Pail

Weight: 35lbs/15.9 KG  
Part #: F230229

#### GreenLube EP-1 Keg

Weight: KG 120 lbs./54 KG  
Part#: 230229

#### GreenLube EP-1 Drum

Weight: 386 lbs./175 KG  
Part#: F230231

#### EP-0 Manual Filler Pump

Format: 5gal/35lb Bucket  
Part#: F190922

#### EP-1 Manual Filler Pump

Format: 5gal/35lb Bucket  
Part#: F801299



| Decription                | EP-0      | EP-1      |
|---------------------------|-----------|-----------|
| NLGI Grade                | 0         | 1         |
| Thickener Type            | Lithium   | Lithium   |
| Dropping Point, C         | 182       | 186       |
| Colour/Texture            | Lt. Green | Amber     |
| Appearance                | Smooth    | Smooth    |
| Copper Corrosion Timken   | 1b        | 1b        |
| EP, Pass, kg (lb)         | 18 (40)   | 22.5 (50) |
| Rust Corrosion            | Pass      | Pass      |
| Base Oil Viscosity @ 40 C | ISO 150   | ISO 220   |

\*GreenLube EP-2 grease available upon request.

